EANARE.

110 ohm AES/EBU Digital Audio Cables (DA202F-2P, DA202F-4P, DA202F-8P)



110 ohm AES/EBU Digital Audio Cables

DA202F-2P, DA202F-4P, DA202F-8P

Product Image

Multi Channel version of DA202. Available in 2, 4 and 8 channel pairs. 25 AWG conductors allow use with Punch Down Block Audio Patchbays. Integral Drain Wire for easy ground wiring. Maximum recommended Length: 180meters. Overall Jacket color: BLUE.

- Twisted Pairs with Braid Shield.
- Special PE Filter Rods maintain constant 110 ohm impedance.
- AES/EBU Digital Audio.
- Audio Rack Wiring.
- Post Productions.
- Digital Mixing System.

EANARE

MECHANICAL SPECIFICATIONS									
Model	Sales Units (m)	Units Inch Ka/100m mm2/(AWC)		Twist Shield On Enrage(Bra Pitch		Unit O.D. (mm)			
DA202F-2P	100	.30 (7.7)	6.2	0.18(25) 7/0.18TA	25	91% or more Spiral Shield			
DA202F-4P	200	.34 (8.8)	.34 10 0.18(25) 8.8) 7/0.18TA		25	91% or more Spiral Shield	d 3.0		
DA202F-8P	500	.45 (11.5)	17	0.18(25) 7/0.18TA	25	91% or more Spiral Shield			

		ELECTR	RICAL P	PERFOR	MANCE			
	Cond. D.C.R.	Shield D.C.R.	Nom. Cap.	Nom. Cap.	Nom. Imp.	Nom. Atten. @3MHz dB/100m	Group Delay Time nS/ft (nS/m)	X-Talk Input 3.31V
Model	ohm/1000ft (ohm/ 100m)	ohm/1000ft (ohm/ 100m)	pF/m	pF/m	ohm			mV/1000ft (mV/ 100m)
DA202F-P Series	<32.3 (<10.6)	<7.0 (<2.3)	23	-	110	5.0	-	-

***Capacitance between conductors.

[†]Capacitance between conductors to shield.

COLORS AVAILABLE										
Model	Black	Blue	Brown	Gray	Green	Orange	Purple	Red	White	Yellow
DA202F-P Series		[+]								

[+]=Standard Color, [o]=Available Color, "- -"=n/a

Phone: 973-837-0070 Fax: 973-837-0080

Copyright (C) 2009 Canare Corporation of America All Rights Reserved.